



High Speed HDMI Cable with Ethernet

HEC, ARC, 3D, 4K@30Hz, HDMI Male to Male, Shielded, Black, 2 m (6.6 ft.)

Part No.: [323215](#)

EAN-13: 0766623323215 | UPC: 766623323215

High Speed Cables deliver high-definition performance

HDMI has become the standard digital connection, delivering the highest-quality audio and video signal over a single cable. Manhattan High Speed HDMI Cables are designed and carefully constructed to meet the evolving needs of the high-definition marketplace. Manhattan High Speed HDMI Cables provide the highest resolution possible at 4K x 2K, an audio return channel and a bandwidth of 10.2 Gbps at 340 MHz. These high-quality cables provide high-definition video and multichannel, digital audio with increased performance characteristics, greater accuracy and expanded features, including Internet connectivity for home entertainment devices using a single HDMI connection.

Features:

- Supports HDMI Ethernet Channel, Audio Return Channel, 3D Video, 4K Display and Deep Color
- High-speed Ethernet, bi-directional networking at up to 100 Mbps
- ARC allows HDMI TV to communicate with home audio systems; no need for additional audio cable
- 4K@30Hz resolution supports video resolution beyond 1080p; up to 1080p resolution in 3D and Deep Color
- Compatible with any HDMI device, such as Blu-ray, game consoles, stereos and PCs
- Compliant with High Speed HDMI specifications
- Up to 10.2 Gbps at 340 MHz bandwidth
- Double shielded to reduce EMI and other interference sources

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Molded PVC boot
- Lifetime Warranty

Specifications:

Standards and Certifications

- ISO 9002

General

- Bandwidth: 10.2 Gbps
- 340 MHz
- HEC support
- Meets or exceeds existing HDMI standards
- Length: 2 m (6.6 ft.)

Contacts

- 2 HDMI 19-pin male
- Nickel-plated contacts
- Molded PVC boot
- Double shielded
- 30-AWG cable

Electrical

- Current rating: 0.5 A DC
- Withstanding voltage: 300 VDC
- Insulation resistance: 50 MOhm
- Conductive resistance: 2 Ohm
- Thermal plastic casing

Package Contents

- High Speed HDMI Cable with Ethernet Channel



