

**Part Number: 5200UP**

Audio Cable, 2 Conductor 16 AWG, BC, Unshielded, CM



## Product Description

Commercial Audio Cable, Rated-CM, 2-16 AWG highly flexible stranded bare copper conductors with PVC insulation, PVC jacket with ripcord

## Technical Specifications

### Product Overview

Environmental Space:	Indoor (Not Riser or Plenum)
----------------------	------------------------------

### Physical Characteristics (Overall)

#### Conductor

AWG	Stranding	Material	No. of Conductors
16	65x34	Bare High-Conductivity ETP Copper	2

Conductor Count:	2
------------------	---

#### Insulation

Material	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.015 in

#### Color Chart

Color
Black
White

#### Outer Shield Material

Material
Unshielded

#### Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness	Ripcord
PVC - Polyvinyl Chloride	0.208 in	0.015 in	Yes

### Construction and Dimensions

#### Cabling

Twists
4.4 twist/ft

### Electrical Characteristics

#### Conductor DCR

Nominal Conductor DCR
4.05 Ohm/1000ft

#### Capacitance

Nom. Capacitance Conductor to Conductor
30 pF/ft

## Inductance

### Nominal Inductance

0.16 µH/ft

## Current

### Max. Recommended Current [A]

15.7 Amps per conductor @ 25°C

## Voltage

### UL Voltage Rating

300 V RMS

## Temperature Range

UL Temp Rating:	75°C
Operating Temp Range:	-20°C To +75°C

## Mechanical Characteristics

Bulk Cable Weight:	25.7 lbs/1000ft
Max Recommended Pulling Tension:	65 lbs
Min Bend Radius/Minor Axis:	2 in

## Standards

NEC/(UL) Specification:	CM
CPR Euroclass:	Eca

## Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

## Flammability, LS0H, Toxicity Testing

UL Flammability:	UL1685 UL Loading
ISO/IEC Flammability:	IEC 60332-1-2
UL voltage rating:	300 V RMS

## Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

## Part Number

### Variants

Item #	Color	UPC	Length	Footnote
5200UP 0101000	Black	612825157694	1,000 ft	
5200UP 010500	Black	612825157670	500 ft	C
5200UP 010U1000	Black	612825157687	1,000 ft	
5200UP 010U500	Black	612825421436	500 ft	
5200UP 010Z1000	Black	612825157571	1,000 ft	
5200UP 010Z1000	Black	612825157571	1,000 ft	
5200UP D151000	Blue	612825157588	1,000 ft	
5200UP D15500	Blue	612825157557	500 ft	C
5200UP D15U1000	Blue	612825157564	1,000 ft	
5200UP D15U500	Blue	612825421405	500 ft	
5200UP D15Z1000	Blue	612825157755	1,000 ft	
5200UP D15Z1000	Blue	612825157755	1,000 ft	

5200UP 0081000	Gray	612825157618	1,000 ft	C
5200UP 008U1000	Gray	612825157625	1,000 ft	
5200UP 008U500	Gray	612825421412	500 ft	
5200UP 008Z1000	Gray	612825157663	1,000 ft	
5200UP 008Z1000	Gray	612825157663	1,000 ft	
5200UP 0051000	Green, Dark	612825157601	1,000 ft	
5200UP 005500	Green, Dark	612825359074	500 ft	
5200UP 005U500	Green, Dark	612825157632	500 ft	
5200UP 0091000	White	612825157649	1,000 ft	C
5200UP 009U1000	White	612825157656	1,000 ft	
5200UP 009U500	White	612825421429	500 ft	
5200UP 009Z1000	White	612825336549	1,000 ft	
5200UP 009Z1000	White	612825336549	1,000 ft	

Footnote:	C - CRATE REEL PUT-UP.
-----------	------------------------

## History

Update and Revision:	Revision Number: 0.265 Revision Date: 08-22-2019
----------------------	--

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.